



SPECIFICATIONS

TYPE: DIGITAL and 15 Character ALPHANUMERIC in Red, Yello	w, G reen or B lue
DISPLAY: 4-DIGIT, 7 seg. TIME in RED and 15 Character 5x7 Dot-Ma	atrix LOCATION in RED
CHARACTER HEIGHT: 1.8" (45.72 mm) HR / MIN 0.7" (17.78mm) LOCATION	
VISIBILITY: 40 Ft. (12.19 MÉTERS)	
POWER REQUIREMENTS: 100-240V 50~60Hz (12vdc Switching Power Supply)	ALL CLOCKS USE THE COLD OF HOLE
FRAME:FINISH)	RTC PARTS, AND OUR FIRMWARE CONTROL
DIMENSIONS: 7.25" x 43.25" x 1.5"	TO GET THE ONE SEC
WEIGHT: 8 lbs.	A YEAR ACCURACY. World's Most Accurate RTC
OPERATING TEMP.: 17° TO 190° F	1 SEC A YEAR ACCURATE (TCXO)
HUMIDITY: 0% TO 95% NON-CONDENSING	
OPERATING MODE: 31 DAY LIGHT SAVINGS, 31 TIME ZONES, 10yr BACKUP WITH 1sec a YEAR ACCURACY,	
NON-GLARE LENS. EYELET AND SAW TOOTH SURFACE MOUNT. PC INTERFACE WITH DDS TIMENET SOFTWARE.	



