

PACIFIC

EASTERN

ZULU

QATAR

UAE

SPECIFICATIONS

BTZ-42418-5

TYPE:---- DIGITAL

DISPLAY: ----- 4-DIGIT, 7 SEGMENT RED SUPER BRIGHT LED

CHARACTER HEIGHT: ----- 1.8" (45.72 mm)

VISIBILITY: ----- 75 Ft. (22.86 MÉTERS)

POWER REQUIREMENTS:--- 110-240V 50~60Hz (12vdc Swithing Power Supply)

FRAME: ----- ALUMINUM (BLACK ANODIZED FĬNISH)

DIMENSIONS: ----- 6.25" x 60.25" x 1.38"

OPERATING TEMP.: ----- -17° TO 180° F

HUMIDITY: ----- 0% TO 95% NON-CONDENSING

OPERATING MODE:----- SYNCHRONIZED ZONES WITH ONE MASTER SET ZONE.

ALL CLOCKS USE THE **DALLAS DS32 SERIES** RTC PARTS, AND OUR FIRMWARE CONTROL, TO GET THE ONE SEC



1 SEC A YEAR ACCURATE (TCXO)



MOUNTING INSTRUCTIONS SECURITY WALL SCREW Frame back



CUSTOM LETTERING TO YOUR SPECIFICATION ALUMINUM FRAME SURFACE MOUNT OR FLUSH 10 YEAR LITHIUM BATTERY BACKUP (Standard) AUTOMATIC DAY LIGHT CORRECTION (Standard) INFRARED REMOTE CONTROL (Standard) ONE SEC A YEAR ACCURACY (TCXO) (Standard)