



SPECIFICATIONS


BTZ-42418-8ERR/MSB-40Y2

TYPE: -----	DIGITAL and 15 LINE ALPHANUMERIC ER= Red EY= Yellow EG= Green EB= Blue
DISPLAY: -----	4-DIGIT, 7 seg. LED, 15 LINE 5 by 7 DOT- MATRIX LED and 40 Character Messge
CHARACTER HEIGHT: -----	1.8" (45.72 mm) HR / MIN 1.2" 15 line location display and Date
VISIBILITY: -----	40 Ft. (12.19 METERS)
POWER REQUIREMENTS: --	100-240V 50~60Hz 9A (12vdc Switching Power Supply).
FRAME: -----	ALUMINUM (BLACK ANODIZED FINISH)
DIMENSIONS: -----	12.25" x 96.25" x 1.35"
WEIGHT: -----	21.25 lbs.
OPERATING TEMP.: -----	-17° TO 190° F
HUMIDITY: -----	0% TO 95% NON-CONDENSING
OPERATING MODE: -----	27 DAY LIGHT SAVINGS, 31TIME ZONES, 10yr BACKUP WITH 1sec A YEAR ACCURACY, NON-GLARE LENS,EYELET AND SAW TOOTH SURFACE MOUNT, PC INTERFACE WITH DDS TimeNet 2.0 SOFTWARE.

ALL CLOCKS USE THE DALLAS DS32 SERIES RTC PARTS, AND OUR FIRMWARE CONTROL, TO GET THE ONE SEC A YEAR ACCURACY.



1 SEC A YEAR ACCURATE (TCXO)



#24awg or larger
twisted pair
SIGNAL CABLE
Category 2 UPT- type


The PC is used to set the Locations and Time. The Clock can run on its own without the PC after setting. NOTE: The colones flashing on zone 1 when it is not running on the PC.



RS-232 SERIAL PORT

DB9 CONNECTOR SUPPLIED

NOT OVER 100ft



MOUNTING INSTRUCTIONS

