



## SPECIFICATIONS

# BTZ- 42425-3/DACY-1T

**TYPE:** ----- DIGITAL  
**DISPLAY:** ----- 4-DIGIT, 7 SEGMENT RED SUPER BRIGHT LED  
**CHARACTER HEIGHT:** ----- 2.5"(63.5 mm) HR./MIN.  
**VISIBILITY:** ----- 150 Ft. (45.72 METERS)  
**POWER REQUIREMENTS:** 100-240V 50~60 Hz (**12vdc Switching Supply**)  
**FRAME:** ----- ALUMINUM (BLACK ANODIZED FINISH)  
**DIMENSIONS:** ----- 10.25 x 38.25 x 1.375  
**WEIGHT:** ----- 7.5 lbs.  
**OPERATING TEMP.:** ----- -17° TO 190° F  
**HUMIDITY:** ----- 0% TO 95% NON-CONDENSING  
**OPERATING MODE:** ----- SYNCHRONIZED ZONES WITH ONE MASTER SET ZONE.

ALL CLOCKS USE THE  
 DALLAS DS32 SERIES  
 RTC PARTS, AND OUR  
 FIRMWARE CONTROL,  
 TO GET THE ONE SEC  
 A YEAR ACCURACY.



**NEW 1 SEC A YEAR ACCURATE (TCXO)**

1.8", 2.5" and 4" DIGIT SIZE  
 12 OR 24 HOUR FORMAT  
 2 TO 24 ZONES  
 NON GLARE LENS  
 SUPER BRIGHT LEDS  
 CUSTOM LETTERING TO YOUR SPECIFICATION  
 ALUMINUM FRAME SURFACE MOUNT OR FLUSH  
 10 YEAR LITHIUM BATTERY BACKUP (**Standard**)  
 AUTOMATIC DAY LIGHT CORRECTION (**Standard**)  
 INFRARED REMOTE CONTROL (**Standard**)  
 ONE SEC A YEAR ACCURACY (TCXO) (**Standard**)

