

## BTZ-42425-3EBR

NUMBER OF ZONES ELECTRONIC LETTERING TIME COLOR

LOCATION COLOR

## **SPECIFICATIONS**

TYPE: ------ DIGITAL and 15 CHARACTER ALPHANUMERIC in (Red, Green, Yellow or Blue)

DISPLAY: ----- 4-DIGIT, 7 seg. TIME in (Red, Green or Blue) and 5 x 7 DOT- MATRIX

CHARACTER HEIGHT: ----- 2.5" (63.5mm) HR / MIN 1.2" (30.48mm) 15 Character location display

VISIBILITY: ----- 85 Ft. (25.90 METERS)

POWER REQUIREMENTS: -- 100-240V 1.5A 47~63 Hz (12vdc SWITCHING POWER SUPPLY).

FRAME: ----- ALUMINUM (BLACK ANODIZED FINISH OR SILVER)

**DIMENSIONS:** ----- 8.25" x 53.25" x 1.38"

**WEIGHT:** ----- 6.7 lbs.

**OPERATING TEMP.:** ----- -17° TO 190° F

HUMIDITY: ----- 0% TO 95% NON-CONDENSING

**OPERATING MODE:** ----- 12 or 24 HR SELECTABLE and AUTOMATIC DAY LIGHTS.

ALL CLOCKS USE THE DALLAS DS32 SERIES RTC PARTS, AND OUR FIRMWARE CONTROL, TO GET THE ONE SEC A YEAR ACCURACY.



1 SEC A YEAR ACCURATE (TCXO)



#24awg or larger twisted pair

SIGNAL CABLE
Category 2 UPT- type

THE PC IS USED TO SET THE LOCATION DISPLAY AND TIME. THE CLOCK CAN RUN ON ITS ON WITHOUT THE PC.





