

## **SPECIFICATIONS**

TYPE: ------ DIGITAL and ALPHA in RED (ER) YELLOW (EY) GREEN (EG) (BLUE (EB)

**DISPLAY:** ----- 4-DIGIT, 7 seg. LED and 15 CHARACTER, 5 by 7 DOT- MATRIX CHARACTER HEIGHT: ----- 2.5" (63.5 mm) HR/MIN *RED*, *GREEN* or *BLUÉ* 1.2" LOCATION **VISIBILITY**: ------ 85Ft. (25.90 METERS)

POWER REQUIREMENTS: ---- 100-240vac 47~63Hz (12vdc Switching Power Supply)

FRAME: ----- ALUMINUM (BLACK ANODIZED FINISH)

DIMENSIONS: ------ 8.25"x 64.25"x 1.5" AND 8.25"x 48.25"x 1.5 (TWO PART)


WEIGHT: ----- 17.8 lbs. TOTAL **OPERATING TEMP.:** ------ -17° TO 190° F

**HUMIDITY**: ------ 0% TO 95% NON-CONDENSING


OPERATING MODE: ------ 27 DAY LIGHT SAVINGS, 31TIME ZONES, 10vr BACKUP WITH 1sec A YEAR ACCURACY, NON-GLARE LENS, EYELET AND SAW TOOTH SURFACE MOUNT, AND PC INTERFACE.


TO GET THE ONE SEC A YEAR ACCURACY. 1 SEC A YEAR ACCURATE (TCXO)


ALL CLOCKS USE THE



THE PC IS USED TO SET THE LOCATION DISPLAY AND TIME. THE CLOCK CAN RUN ON ITS ON WITHOUT THE PC.








AND THE COLON IS FLASHING ON (0).

**VERTICAL LAYOUT (16.5" x 69.25" x 1.375)** 



GROUP CLOCK NUMBERS HORIZONTAL LAYOUT (8.25" x 122.5" x 1.375)

