



SPECIFICATIONS

BTZ-42425-8

TYPE: -----	DIGITAL
DISPLAY: -----	4-DIGIT, 7 SEGMENT RED SUPER BRIGHT LED
CHARACTER HEIGHT: -----	2.5"(63.5 mm) HR./MIN.
VISIBILITY: -----	150 Ft. (45.72 METERS)
POWER REQUIREMENTS: -----	110-240V 50~60Hz (12vdc Switching Power Supply)
FRAME: -----	ALUMINUM (BLACK ANODIZED FINISH)
DIMENSIONS: -----	7.25" x 96.25" x 1.375"
WEIGHT: -----	17.5 lbs.
OPERATING TEMP.: -----	-17° TO 190° F
HUMIDITY: -----	0% TO 95% NON-CONDENSING
OPERATING MODE: -----	SYNCHRONIZED ZONES WITH ONE MASTER SET ZONE.



1 SEC A YEAR ACCURATE (TCXO)

- 1.8", 2.5" and 4" DIGIT SIZE
- 12 OR 24 HOUR FORMAT
- 2 TO 24 ZONES
- NON GLARE LENS
- SUPER BRIGHT LEDS
- CUSTOM LETTERING TO YOUR SPECIFICATION
- ALUMINUM FRAME SURFACE MOUNT OR FLUSH
- 10 YEAR LITHIUM BATTERY BACKUP **(Standard)**
- AUTOMATIC DAY LIGHT CORRECTION **(Standard)**
- INFRARED REMOTE CONTROL **(Standard)**
- ONE SEC A YEAR ACCURACY (TCXO) **(Standard)**

