WALL MOUNT



SPECIFICATIONS

NON GLARE LENS
SUPER BRIGHT LEDS
ALUMINUM FRAME
10 YEAR LITHIUM BATTERY BACKUP (Standard)

AUTOMATIC DAY LIGHT CORRECTION (Standard)
ONE SEC A YEAR ACCURACY (TCXO) (Standard)

· · · · — ·	DIOTIAL
DISPLAY:	4-DIGIT, 7 SEGMENT LED (SUPER BRIGHT)
	7" (177.8 Millmeters) HR / MIN
VISIBILITY:	500 Ft. (152.4 Meters)
POWER REQUIREMENTS:	100-240 V 47~63Hz (12vdc SWITCHING POWER SUPPLY)
	ALUMINUM (BLACK ANODIZED FINISH)
DIMENSIONS:	12.25" x 28.25" x 5"
WEIGHT:	22 lbs

WEIGHT: ----- 22 lbs.

OPERATING TEMP.: ----- -17° TO 150° F

HUMIDITY: ----- 0% TO 95% NON-CONDENSING

----- DIGITAL

OPERATING MODE:------ 12/24 HOUR, AUTOMATIC DAY LIGHT, 10 YEAR

LITHIUM BATTERY BACKUP.

TYPF.