



DTZ-42420-4ERR


SPECIFICATIONS





| | |
|--|---|
| TYPE: | LED 15 CHARACTER ALPHANUMERIC (AVAILABLE IN Red, Green, Yellow or Blue) |
| DISPLAY: | 4-DIGIT TIME 5 by 7 DOT-MATRIX (AVAILABLE IN Red, Green, Yellow or Blue) |
| CHARACTER HEIGHT: | 2"(50.8 mm) TIME HR/MIN 1.2"(25.4mm) 15 CHARACTER LOCATION DISPLAY |
| VISIBILITY: | 75 Ft. (22.86 METERS) |
| POWER REQUIREMENTS: | 100-240V 50~60Hz (12vdc SWITCHING POWER SUPPLY). |
| FRAME: | ALUMINUM (BLACK ANODIZED FINISH) |
| DIMENSIONS: | 8.25" x 64.25" x 1.35" |
| WEIGHT: | 23.25 lbs. |
| OPERATING TEMP.: | -17° TO 190° F |
| HUMIDITY: | 0% TO 95% NON-CONDENSING |
| OPERATING MODE: | 31 DAY LIGHT SAVINGS, 31TIME ZONES,10 YEAR BACKUP WITH UP TWO ONE |
| SECOND A YEAR ACCURACY, EYELET SURFACE or CEILING MOUNT, PC INTERFACE WITH DDS SOFTWARE | |



1 SEC A YEAR ACCURATE (TCXO)




THE PC IS USED TO SET THE LOCATION DISPLAY AND TIME. THE CLOCK CAN RUN ON ITS ON WITHOUT THE PC.





**RS-232 SERIAL
PORT**

**DB9
CONNECTOR
SUPPLIED**



DDSTimeNet from Digital Display Systems

Group Letter: **A** Group Clock Numbers: **0** Presets... Help...

Time Zone: **(24) UTC-8 (Uniform) PST Pacific Standard Time**

Daylight Savings: **(30) 2nd Sunday in Mar. 0159-0300 to 1st Sunday in Nov. 0159-0100**

Text Display: **CALIFORNIA** Cancel Apply Exit

Sending to Clock Number 1 Using COM1 Thu, Jan 17, 2008 10:38:26

**RS-232
NOT OVER
100ft**

**(+) SIDE
BLUE / WHITE
ORANGE / WHITE**

For all system wiring
uses Wire-Nuts
SIZE 72B

**(-) SIDE
WHITE / BLUE
WHITE / ORANGE**

**ALL CLOCKS USE THE
DALLAS DS32 SERIES
RTC PARTS, AND OUR
FIRMWARE CONTROL,
TO GET THE ONE SEC
A YEAR ACCURACY.**



1 SEC A YEAR ACCURATE (TCXO)

**WHEN ON THE PC THE PC TIME IS UP
DATING THE TIME ON THE TIME ZONE
CLOCKS. WHEN THE PC IS OFF THE (0)
ZONE IS UPDATING THE TIME AND THE
COLON IS FLASHING ON ZONE (0).**

GROUP CLOCK NUMBERS

0

1

2

3

10:45

CALIFORNIA

12:45

HOUSTON

13:45

WASHINGTON, DC

18:45

LONDON