



CEILING MOUNT
HARDWARE INCLUDED

DDS IR REMOTE SENSOR
When using remote to set clock,
point remote at DDS sticker on left corner.

DSA-62470-4-IRR

SPECIFICATIONS

TYPE: ----- DIGITAL
DISPLAY: ----- 4-DIGIT, 7 SEGMENT RED LED
CHARACTER HEIGHT: ----- 7" (188.8mm) HR/MIN/sec
VISIBILITY: ----- 500 + Ft. (150.4 METERS)
POWER REQUIREMENTS: -- 100-240V 50~60Hz (**Switching Power Supply**)
FRAME: ----- ALUMINUM (BLACK ANODIZED FINISH)
DIMENSIONS: ----- 43.75" x 43.75" x 10.75"
WEIGHT: ----- 40 lbs.
OPERATING TEMP.: ----- -17° TO 150° F
HUMIDITY: ----- 0% TO 95% NON-CONDENSING



12 OR 24 HOUR FORMAT
 NON GLARE LENS
 SUPER BRIGHT LEDES
 ALUMINUM FRAME

10 YEAR LITHIUM BATTERY BACKUP (**Standard**)
 AUTOMATIC DAY LIGHT CORRECTION (**Standard**)
 ONE SEC A YEAR ACCURACY (TCXO) (**Standard**)

ALL CLOCKS USE THE
 DALLAS DS32 SERIES
 RTC PARTS, AND OUR
 FIRMWARE CONTROL,
 TO GET THE ONE SEC
 A YEAR ACCURACY.



1 SEC A YEAR ACCURATE (TCXO)

CEILING MOUNT INSTALLATION INSTRUCTIONS

