

3:28
PACIFIC

4:28
MOUNTAIN

5:28
CENTRAL

6:28
EASTERN

11:28
ZULU

10:28
LOCAL

DTZ-42420-6ERR


DIGIT SIZE	NUMBER OF ZONES	ELECTRONIC LETTERING	TIME COLOR	LOCATION COLOR
------------	-----------------	----------------------	------------	----------------

SPECIFICATIONS



TYPE: ----- DIGITAL and ALPHANUMERIC in *Red, Yellow, Green, or Blue*
DISPLAY: ----- 5x7 Dot-Matrix 4-digit **TIME** in **RED** and 15-character **LOCATION** in **RED**
CHARACTER HEIGHT: ----- 2" (50.8 mm) HR/MIN 1.2" (25.4mm) LOCATION
VISIBILITY: ----- 75 Ft. (22.86 METERS)
POWER REQUIREMENTS: ----- 100-240V 50~60Hz (**12vdc SWITCHING POWER SUPPLY**)
FRAME: ----- ALUMINUM (**BLACK ANODIZED FINISH**)
DIMENSIONS: ----- 96.25" x 7.25" x 1.5"
WEIGHT: ----- 16 lbs.
OPERATING TEMP.: ----- -17° TO 190° F
HUMIDITY: ----- 0% TO 95% NON-CONDENSING
OPERATING MODE: ----- AUTOMATIC DAY LIGHT SAVINGS, 31 TIME ZONES, 10yr BACKUP WITH 1sec A YEAR ACCURACY, EYELET AND SAW TOOTH SURFACE MOUNT, PC INTERFACE WITH DDS TimeNet SOFTWARE. RS-232 DB9 SERIAL PORT 100ft




1 SEC A YEAR ACCURATE (TCXO)




THE PC IS USED TO SET THE LOCATION DISPLAY AND TIME. THE CLOCK CAN RUN ON ITS OWN WITHOUT THE PC.





RS-232 SERIAL PORT
DB9 CONNECTOR SUPPLIED



RS-232 NOT OVER 100ft

(+) SIDE
 BLUE / WHITE
 ORANGE / WHITE

For all system wiring uses Wire-Nuts SIZE 72B

(-) SIDE
 WHITE / BLUE
 WHITE / ORANGE



1 SEC A YEAR ACCURATE (TCXO)

WHEN ON THE PC THE PC TIME IS UP DATING THE TIME ON THE TIME ZONE CLOCKS. WHEN THE PC IS OFF THE (0) ZONE IS UPDATING THE TIME ZONES AND THE COLON IS FLASHING ON (0).

GROUP CLOCK NUMBERS

